



PRODUCT SPECIFICATIONS

AlumiGraphics® Grip is a printable media for wide format digital printers that applies direct to an infinite variety of surfaces including sealed and unsealed concrete, asphalt, brick, tile, terrazzo, marble, and vinyl flooring as well as brick, stucco, cinderblock and other exterior masonry wall surfaces.

Differentiators of AlumiGraphics® Grip over vinyl media, stenciling, chalk and painting

- Rugged **aluminum foil material** naturally conforms to the texture of rough or smooth surfaces, appears as a painted graphic
- **Wide 53 inch media** provides greater coverage and production yield; available in 30', 75' and 150' rolls
- Print direct to the uniquely textured surface; **no over laminate required**
- High friction surface provides dual characteristics of **exceptional slip resistance** exceeding international anti-slip standards and **reflectivity** for excellent nighttime visibility
- Proven durability for short term and long term use that **withstands heavy pedestrian traffic** in hot, cold and wet weather environments for up to 1 year
- **Easy installation and removal** with a high performance pressure sensitive adhesive; sweep the surface, peel off the liner and apply to the desired surface
- **Pressure sensitive acrylic adhesive** backing provides superior holding strength and does not require professional installation
- Simple peel off removal with typically **no residue remaining** on surface
- Contains no PVC or hazardous ingredients and can be **disposed with aluminum recycling**

Types of Printers & Results

- UV Curing = best print & color quality plus longevity
- Latex (new models) = great imprint and cost efficient
- Solvent = lighter color saturation, less vibrant imprint, and good short term

Physical Properties

Thickness:	
Film	16 mil.
Adhesive	2 mil.
Liner	5 mil.



Manufactured by FloorSignage, LLC
visit online www.FloorSignage.com
or www.AlumiGraphics.com
call toll free (855) 855-8832



PRODUCT SPECIFICATIONS

Storage

Product can safely be stored for twelve (12) months in original packaging, laying flat in a cool, dry area
50° – 90°F / 10° - 32°C.

Service Temperature Range

-40° - 176°F / -40°C - 80°C

Minimum Application Temperature

32°F / 0°C or warmer

Sign Ordinance Compliance

AlumiGraphics® Grip is landscape friendly signage that is perfect in locations with restrictions or ordinances on vertical signs and is also an alternative to banners

Suggested Applications

- Sidewalks & Walkways
- Entrances & Vestibules
- Stairs, Aisles & Rows
- Patios & Courtyards
- Elevator & Escalator Entries
- Parking Spaces & Curbs
- Factory & Warehouse
- Concourse & Landings
- Exterior Walls & Facades

Locations

- Stores & Shopping Malls
- Airports & Transit Facilities
- Races, Walks & Marathons
- Concert & Theater Venues
- Colleges & Universities
- Amusement Parks & Fairs
- Stadiums & Arenas
- Corporate Offices
- Special Events
- Warehouse & Manufacturing
- Museums & Zoos
- Golf Course / Tennis Centers
- Restaurants & Bars
- Govt. & Military Facilities
- Hospitals & Medical Centers
- Bike / Walk Paths & Parks
- Car Parks & Garages
- Schools & Churches

Warranty

The following is made in lieu of all warranties, expressed or implied: the Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use. There are no guarantees or warranties of any kind to the suitability or performance for specific applications. The user assumes all risk and liability, whatsoever, in connection therewith. The warranty is exclusive. In no case shall the Seller or Manufacturer be liable for any other direct or indirect damages or loss, including without limitation any incidental, special, or consequential damages, or any labor charges incident to the removal or replacement of the graphic. The foregoing may not be changed except by written agreement by the manufacturer.